



TO ACCEPT A 2 7/8" O.D.
TENON x 3 1/2" LONG

3/8-16 ST. STL.
BLACK HEX HEAD BOLTS

NOTE:
 ALL THUMB SCREWS WOULD BE REPLACED BY HEX HEAD BOLTS
 **ANTI SIEZE COMPOUND MUST BE APPLIED TO ALL THREADED BOLTS
 PRIOR TO INSTALLATION AT FACTORY**

| REV. | ALTERATION | DATE | BY |
|------|------------|------|----|
| | | | |

LUMINAIRE SPECIFICATIONS

CATALOGUE NO.: K137-P4NG-IV-75(SSL)-7030
-120:277-K14-PR7-3K-#1-WS

QUANTITY:
 OPTICAL SYSTEM: FLAT ARRAY (NO GLOBE)
 IES CLASS.: TYPE IV
 INPUT WATTAGE: 75W (7030 SERIES)
 SOLID STATE LIGHTING
 LINE VOLTAGE: 120:277V
 CCT: 3000K
 POLE ADAPTOR K14
 PAINT: TEXTURED BLACK
 OPTIONS: C/W TWISTLOCK RECEPTACLE
 (PHOTO-EYE BY OTHERS),
 WATTAGE SELECTOR & #1 FINIAL

OPTIONS:
 QUICK DISCONNECT

CUSTOMER APPROVAL & DATE: _____

| | |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
|   King Luminaire • StressCrete • Est. 1953 STRESSCRETE GROUP | <u>Manufacturing Locations:</u> |
| | Burlington, Ontario 1-800-268-7809 Northport, Alabama 1-800-435-6563 Atchison, Kansas 1-800-837-1024 Jefferson, Ohio 1-800-268-7809 |

CUSTOMER ORDER No:
 STRESSCRETE ORDER No:
 KING U.S. ORDER No:

PROJECT/CUSTOMER:
LCEC K137NG

| | | | | |
|-------------------------------------|------------|-------------|--------------------------------|-----------|
| DRAWN BY: J.H. | AT: SC1 | CHECKED BY: | DATE: 03/19/24 | REVISION: |
| DRAWING TYPE: APPROVAL/MFG. DWG. | | | DRAWING NUMBER: Q-2403057-1 | |